



24-port Modular L2 Managed Gigabit Switch



Ethernet Module GS08R

Fiber Module GS08F

- Provide 24+4 full Gigabit Ethernet or optical fiber ports.
- Ethernet ports support 10/100/1000Mbps, downlink optical fiber ports support 100/1000Mbps SFP module.
- 1-24 downlink ports support hot pluggable Ethernet or optical fiber modules and support Mixed Ethernet and optical modules, which is very convenient for mixed application of Ethernet and optical fiber.
- Provide web-based layer 2 network management and PoE management, simple operation.
- Support high-speed data forwarding, very suitable for large flow of video data forwarding in security surveillance.
- Support recovery of IP address & user password with one key recovery button.
- Provide two power supply redundancy backup to improve system reliability.
- Quick Installation, simple operation, convenient for wall, desk or rack installation.

Technical Specifications

Ethernet Port	1 ~ 24 Ports: 10/100/1000Mbps Ethernet port, adaptive control UPLINK Ethernet port: 10/100/1000Mbps adaptive Ethernet port SFP: SFP optical fiber module, 1000Mbps
Transmission Distance	1 ~ 24 ports: Recommended 100m Uplink 1000Mbps Ethernet port: Max.100m SFP: depend on the optical module performance
Ethernet Standard	IEEE802.3 10BASE-T, IEEE802.3u 100BASE-TX, IEEE802.3ab 1000BASE-T, IEEE802.3z 1000BASE-SX/LX, IEEE802.3X, IEEE802.1Q IEEE802.1p, IEEE802.3ad
Switch Capacity	70G
MAC Address	16k
Management	L2
ESD Protection	Level 3, IEC61000-4-2
Lightning Protection	Level 3, IEC61000-4-5
Power Supply	AC 100~240VAC, 2 x 60W
Working Conditions	0°C ~ 55°C, 0 ~ 95% Humidity
Dimensions	442 x 315 x 44.5 mm
Weight	3.8 kg