



## 24-port L3 Managed Gigabit Ethernet Switch



- 24 nos. 10/100/1000 Base-T ports + 4 nos. 10GBase-X SFP+ ports.
- Provide web-based layer 3 network management.
- Support high-speed data forwarding, perfectly designed for large flow of video data forwarding in security surveillance.
- Support QoS, VLAN and Storm Suppression
- Support fast ring ,Self-healing in 20ms
- Excellent circuit isolation protection, lightning protection up to 6 kV in accordance to IEC 61000-4-5.
- Quick installation, easy operation and convenient for wall/ desk/ rack installation.

### Technical Specifications

<b>Ethernet Port</b>	Port 1 ~ 24: 10/100/1000 Mbps Ethernet port, self-adaptive control Port 25 & 26: 1000 Base-X SFP port
<b>Transmission Distance</b>	Port 1 ~ 24: Recommended 100m, max.100m SFP: depend on the optical module performance
<b>Ethernet Standard</b>	IEEE 802.3u 100BASE-TX IEEE802.3ab 1000BASE-T, IEEE802.3z 1000BASE-SX/LX IEEE802.3ad, Static or Dynamic Link Aggregation IEEE802.3x, Full Duplex Flow Control, IEEE802.3az, EEE (Energy Efficient Ethernet) IEEE802.1q, VLAN (up to 4096 VLANs, Port Based) IEEE802.1p, QoS / CoS IEEE802.1d, STP (Spanning Tree Protocol) IEEE802.1w, RSTP (Rapid Spanning Tree Protocol)
<b>Switch Capacity</b>	128 Gbps, 96 Mpps throughput
<b>Management</b>	L3
<b>MAC Address Table</b>	Up to 16k MAC addresses, auto-update two-way learning
<b>ESD Protection</b>	6kV contact discharge, 8kV air discharge; IEC61000-4-2
<b>Lightning Protection</b>	6kV, IEC61000-4-5
<b>Power Supply</b>	AC 90~264VAC, 420VA (Full Load)
<b>Working Conditions</b>	-10°C ~ 50°C, 5 ~ 95% Humidity
<b>Dimensions</b>	442 x 305 x 44.5 mm
<b>Weight</b>	4.35 kg