


## Embedded Network Video Recorder



- Up to 8 / 16 IP camera input
- Supports ONVIF compliant IP cameras
- Up to 5MP resolution recording
- HDMI & VGA output up to 1920 x 1080p resolution
- Smart HDD quota & group management
- 2 SATA slots, 2 USB2.0 ports
- 8 independent PoE network interface (INV208P, INV216P)
- Multi-level user management with password protection

### Technical Specifications

	INV208	INV216
IP Video Input	8 Ch	16 Ch
Two-way Audio	1 Ch, BNC (2.0Vpp, 1kΩ)	
Recording Resolution	5MP, 3MP, 1080p, UXGA, 720p, VGA, 4CIF, DCIF, 2CIF, QCIF	
CVBS Output	1 Ch, BNC (1.0Vpp, 75Ω) Resolution 704 x 576 (PAL), 704 x 480 (NTSC)	
HDMI Output	1920 x 1080p, 1600 x 1200, 1280 x 1024, 1280 x 720, 1024 x 768	
VGA Output	1 Ch, Resolution 1920 x 1080p, 1600 x 1200, 1280 x 1024, 1280 x 720, 1024 x 768	
Audio Output	1 Ch, BNC (Linear, 600Ω)	
Playback Resolution	5MP, 3MP, 1080p, UXGA, 720p, VGA, 4CIF, DCIF, 2CIF, CIF, QCIF	
Synchronous Playback	8 Ch	16 Ch
Hard Disk	2 SATA interface for 2 HDD	
eSATA	None	
Capacity	Up to 4TB capacity for each HDD	
Network Interface	1 RJ-45 10/100/1000 Mbps self-adaptive ethernet interface	
Serial Interface	1 RS-232 interface (for parameters configuration, maintenance) 1 RS-485 interface (reserved)	
USB Interface	2 x USB2.0	
Alarm	4 In / 2 Out	
Power Supply	12VDC	
Power Consumption	< , = 13W (w/o HDD or DVD-R/W)	
Operating Conditions	-10°C - 55°C, Humidity 10% ~ 90% (non-condensing)	
Dimension	445 x 261 x 44.5 mm	
Weight	<4 kg (<8.82 lbs) (without hard Disk or DVD-R/W)	