



## Network Keyboard Controller

- Ergonomic design with 800×480 LCD touch panel
- Live view and playback of video on screen at up to 1080p
- 1-channel video decoding for local live view
- Video capture and recording to local U-flash disk
- Play back record files from the U-flash disk
- Play back remote recorded files by time or by file
- 7" TFT touch screen at 800×480 resolution
- Support 15 operators, and each user is allowed to operate 256 devices with up to 4096 channels
- 4-axis joystick
- Shortcut keys for:
  - Dome control, setting and calling of preset, patrol and pattern
  - playback operation
  - input group and output group
  - wiper and light control operation
- Auto searching connected devices in the same network area
- Two-way audio
- Support configuration by WEB server
- Support configuration by the Keyboard Configuration Tool
- Configuration and control of the matrix system
- Control of up to 255 analog domes by RS-485 connection
- Provide 1-ch video decoding and local decoding
- Support standard MPEG4, private H.264 and standard H.264 encoding formats

### Technical Specifications

<b>Control Mode</b>	IP Based - 7" TFT LCD Monitor with touch panel
<b>TFT LCD Panel</b>	Resolution: 800 x 480
<b>Joystick</b>	4-axis joystick
<b>Audio Input/Output</b>	Line In: 1 Ch, 3.5mm connector (2.0Vp-p, 1 kΩ) Audio Out: 1-ch, 3.5mm connector (Linear, 560Ω)
<b>External Interface</b>	Network - 1 10/100/1000M Ethernet interface 1 RS-232 & 1 RS-485 1 USB2.0 (for data storage and device upgrade)
<b>Power Supply</b>	12 Vdc
<b>Power Consumption</b>	< 15W
<b>Working Temperature</b>	-10°C ~ +55°C
<b>Working Humidity</b>	10% ~ 90%
<b>Dimensions</b>	193 x 435 x 110 mm
<b>Weight</b>	2 kg