



**VMT300** - Visitor Management System Terminal

## VMT300

### Visitor Management System Terminal

- 15.6-inch main screen and 11.6-inch auxiliary screen.
- Main screen support touch screen.
- Front-facing dual 2MP HD camera for capturing visitor face image.
- Supplementary light for use in dark-environment.
- Adjustable camera angle for variable visitor height.
- Built-in Mifare / EM card enrollment reader for issuance of visitor pass.
- Dual network interface that supports TCP/IP communication protocol.
- Built-in barcode & QR code scanner for reading pre-registered tickets.
- Built-in thermal printer for printing of visitor pass.

### Technical Specification

|                     |  |
|---------------------|--|
| Operating System    | Windows 10   |
| Hardware            | Intel Quad-Core Processor 2.0 GHz CPU  |
| Storage             | 64 Gb SSD; 4GB DDR3 RAM  |
| Display Screen      | Main Screen: 15.6-inch 1920 x 1080 Touch Screen<br>Auxiliary Screen: 11.6-inch 1366 x 768 Screen |
| Camera              | Dual 2MP   |
| Csrd Format         | Mifare Card or EM Card   |
| Printer             | 58mm Thermal Printer, max 45mm roll dia  |
| Code Scanner        | Bar Code or QR Code  |
| Communication       | 10/100Base-T x 2   |
| USB Interface       | 2 nos.   |
| Input Voltage       | 85 to 264 Vac  |
| Output Voltage      | 12V, 8.33A   |
| Working Temperature | -10°C ~ 55°C   |
| Working Humidity    | 10% ~ 90% (non-condensing)   |
| Working Condition   | Indoor   |
| Weight              | 17.64 kg   |
| Dimensions (WxHxD)  | 400 x 426 x 390 mm   |

\* Technical specifications and images are subject to changes  
© 2019 PIXELab. All rights reserved