

Network Keyboard Controller



- 10.1" capacitive touchscreen (1280 x 800 resolution) with live view on touch panel. DVI and HDMI output to monitor.
- 4-axis joystick for PTZ control, setting and calling preset, patrol and pattern. Controllable of 8000 devices.
- Detachable design of the touchscreen and joystick.
- Wired and WiFi network connection.
- POE power supply.
- Capable of decoding 2-ch at 1080P decoding; up to 16-division window display.
- Direct access to DVR, DVS, NVR, network camera & speed dome and accessible to ISM Software.
- Control of MVC and decoders for video decoding and output on video wall.
- Add cameras in batches by importing an Excel file from a USB drive and support upgrade and configuration files import/export by USB flash disk.
- Support recording and picture capturing; saving files in USB flash disk or uploading to FTP server.
- Two-level user authority and up to 32 user accounts are configurable: one admin and 31 operators.

Technical Specifications

Operating System	Android 6.0
LCD Screen	10.1" TFT LCD Touchscreen, 1280 x 800 resolution
Joystick	4-axis joystick
Local Decoding	Live View at 1080p, 720p, HD1, BCIF, CIF, QCIF up to 16-division window display
Two-way Audio Input	1 ch, 3.5mm connector (2.0Vp-p, >1kW)
Network Interface	10/100/1000M Adaptive Ethernet interface
WiFi	Support
USB Interface	2 x USB2.0 (for data storage and device upgrade)
Video Interface	HDMI, DVI
Power Supply	12 Vdc / PoE
Power Consumption	< 15W
Working Temperature	-10°C ~ +55°C
Working Humidity	10% ~ 90%
Dimensions	404 x 180 x 163 mm
Weight	1.7 kg